

MECHANIC FILTRATION SYSTEMS

- AQUALINE BAG FILTERS
- AQUALINE SEPARATOR FILTERS
- AQUALINE CARDRIDGE FILTERS



PVC BAG FILTERS



SS304 BAG FILTER



SP350 - SP800



SPARE BAG
FILTERS

AQUALINE BAG FILTER SYSTEMS

MODEL	CONNECTION	CAPACITY (m ³ /h)	DIMENSIONS (mm)	WEIGHT (kg)
AQUALINE PVC BAG FILTER SYSTEMS				
PVC732 AYB	2" (DN50)	10	400 x 420 x 1180	18
STAINLESS BAG FILTERS (SS304, SS316)				
ABF732	2" (DN50) GEAR	10	430 x 440 x 1075	32
ABF3 x 732	3" (DN80) GEAR	30	625 x 660 x 1180	100
SPARE BAG FILTERS				
MODEL	DIMENSIONS (mm)		MICRON RATING	
7" - 32"	170 x 820		5 - 10 - 25 - 50 - 100 - 200 Micron	

SEPARATOR FILTERS

MODEL	CONNECTION	FLOW RATE (m ³ /h)	DIMENSIONS (mm)	WEIGHT (kg)
SS304, SS316 STAINLESS STEEL / ST-37 CARBON STEEL (EPOXI PAINTED)				
AQUALINE SP 100	1/2" (DN15)	1-1,5	780 x 176 x 140	6
AQUALINE SP 150	3/4" (DN20)	2-7,5	780 x 176 x 140	6
AQUALINE SP 175	1" (DN25)	6,5-11	775 x 208 x 168	7,7
AQUALINE SP 200	1 1/4" (DN32)	10-16	775 x 223 x 168	9
AQUALINE SP 250	1 1/2" (DN40)	14,5-18	775 x 223 x 168	10
AQUALINE SP 350	2" (DN50)	17-24,5	1185 x 450 x 410	18,5
AQUALINE SP 450	2 1/2" (DN65)	22-35	1185 x 450 x 410	19
AQUALINE SP 600	3" (DN80)	33,5-66	1430 x 520 x 470	29,3
AQUALINE SP 800	4" (DN100)	64-110	1720 x 540 x 485	50,5

Operating Pressure: 6-8 bar (Max.) Drain Line: For all models 1" Micron Range: 70-110 Micron

MORE INFO



MECHANIC FILTRATION SYSTEMS



SPUN FILTERS



MODEL PVC5



MODEL PVC9



MODEL ACF

AQUALINE CARTRIDGE FILTERS

MODEL	CONNECTION	CARTRIDGE QTY	CARTRIDGE LENGTH	DIMENSIONS (mm)	WEIGHT (kg)	FLOW RATE (m ³ /h)				
						1μ	5μ	10μ	25μ	50μ

PVC MULTI-CARTRIDGE FILTERS

PVC 520 - AYB	DN50	5	20"	300 x 300 x 720	13	5	10	15	20	24
PVC 530 - AYB	DN50	5	30"	300 x 300 x 1000	14,5	7,5	15	22,5	23	24
PVC 540 - AYB	DN50	5	40"	300 x 300 x 1200	16,5	10	20	23	23	24
PVC 930 - AYB	DN80	9	30"	400 x 400 x 1000	26	13,5	27	40,5	54	54
PVC 940 - AYB	DN80	9	40"	400 x 400 x 1200	31	18	36	54	55	54

Operating Pressure: 5 bar (Max) Body: PVC Material Filtration Range 1 - 25 Micron

STAINLESS STEEL MULTI-CARTRIDGE FILTERS

ACF 320	2"(DN50)	3	20"	375 x 426 x 954	19	3	6	9	12	18
ACF 330	2"(DN50)	3	30"	375 x 426 x 1200	22	5	9	14	20	24
ACF 340	2"(DN50)	3	40"	375 x 426 x 1250	24	6	12	18	24	24
ACF 520	2"(DN50)	5	20"	425 x 470 x 973	23	5	10	15	20	24
ACF 530	2"(DN50)	5	30"	425 x 470 x 1223	27	8	15	24	24	24
ACF 540	2"(DN50)	5	40"	425 x 470 x 1473	32	10	20	24	24	24
ACF 830	2 1/2"(DN65)	8	30"	435 x 440 x 1235	37	12	24	36	48	54
ACF 840	2 1/2"(DN65)	8	40"	435 x 440 x 1485	44	16	32	48	54	54
ACF 1230	3"(DN80)	12	30"	490 x 485 x 1238	49	18	36	54	54	54
ACF 1240	3"(DN80)	12	40"	490 x 485 x 1538	58	24	48	54	54	54
ACF 1640	4"(DN100)	16	40"	595 x 600 x 1550	82	32	64	92	92	92
ACF 2740	5"(DN125)	27	40"	790 x 790 x 1574	115	54	108	140	140	140

Operating Pressure: 7 bar (Max) Body: AISI 304 Stainless Steel Filtration Range: 1 - 25 Micron